



## CAMERALINK

# Wirelessly connect your camera to SlingStudio.

Use your HDMI camera or camcorder to wirelessly send video to SlingStudio.™ CameraLink gives you professional-quality content by sending up to 1080p60 video at up to 30 Mbps using H.264 encoding.



### AUDIO & VIDEO INPUT

---

#### HDMI and Digital Audio

1 HDMI Type D connector supporting 1080p60, 1080i60, 1080p30, 720p60, and 720p30 video inputs

2-channel HDMI embedded audio (48 KHz, 44.1 KHz, 36 KHz, 16-bit)

### BROADCASTING FORMAT

---

#### Video Encoding

H.264 High Profile 4:2:0  
1080p60 up to 30 Mbps  
1080p30 up to 16 Mbps  
720p60 up to 16 Mbps  
720p30 up to 4 Mbps

#### Audio Encoding

AAC-LC at 320 kb/s  
2-channel 48 KHz, 16-bit

#### Compatibility

Supported\* cameras and camcorders with an HDMI output for wirelessly sending video and audio to SlingStudio

*\*See supported devices at [MySlingStudio.com/compatibility](http://MySlingStudio.com/compatibility).*

## BATTERY & CHARGING

---

<b>Battery Life</b>	2+ hours
<b>Battery Charging</b>	Micro-USB charging port for use with common smartphone/tablet USB cables
<b>Charging Time</b>	3 to 4 hours when CameraLink is off using a USB cable with 10 W (5V, 2A) or higher

## HARDWARE

---

<b>Wireless</b>	802.11ac – used to transmit encoded video from camera/camcorder to SlingStudio
<b>Interfaces</b>	HDMI Type D input supporting both interlaced and progressive formats (1080p60, 1080i60, 1080p30, 720p30, 720p60) Micro-USB input (for charging via USB)
<b>LED Indicators</b>	4 battery status LEDs 1 Micro-USB charging LED 1 power status LED 1 program tally LED
<b>Power Status LED</b>	Blinking Red: Pairing/WPS mode Solid White: Connected to SlingStudio Blinking White and Program Tally LED is Blinking White: Powering on Blinking White and Program Tally LED is Off: Powered on and looking to connect
<b>Program Tally LED</b>	Solid Orange: CameraLink is live/on-program/on-air Off: CameraLink is not live/on-program/on-air
<b>Buttons</b>	Power on/off button Reset button (pinhole)
<b>Physical Attributes</b>	(H) 35 mm x (W) 115.8 mm x (D) 72.8 mm Weight: 0.6 lbs (270 g)
<b>Battery</b>	Lithium-ion 3.7 V, 3100 mAH battery
<b>Operating Temperature</b>	32°F to 95°F (0° to 35°C)
<b>Humidity</b>	0 to 95% (non-condensing)

## ACCESSORIES

---

<b>In the Box</b>	Hot shoe mount Micro-USB cable HDMI Type D-to-HDMI Type C cable
<b>Sold Separately</b>	HDMI Type D-to-HDMI Type A cable HDMI Type D-to-HDMI Type D cable