Ongenieux[®]



Compatible with lightweight Optimo line:
Optimo 45-120, Optimo 28-76,
Optimo 15-40 for Film and Digital cinema,
Optimo DP 16-42 and Optimo DP 30-80
for Digital Cinema.

Optimo Servo Unit provides control of Zoom and Iris. Focus control will only be available with specific versions. Servo Unit also allows communication with certain cameras such as the capability of remote iris position control.



Optimo Servo Unit technical specifications





Weight

700g / 1.5 lbs

Compatible with

Optimo 15-40

Optimo 28-76

Optimo 45-120

Optimo DP 16-42

Optimo DP 30-80

Control of

Zoom

Iris

Focus (specific version)

Communication (depending on versions)

With different camera protocols (including Cooke protocol)

With Angenieux remote control protocol

The Optimo Servo Unit has been specifically designed for the "run and gun" style of shooting and to work in conjunction with high end film or digital production equipment. Cinematographers can now benefit from the ease of use and accuracy of zoom control right at their fingertips.

Thales Angenieux in the USA 40G Commerce Way

Totowa NJ 07512 - USA Phone: 1 973 812 3858 Fax: 1 973 812 9049 angenieux@tccus.com Thales Angenieux Headquarters

Boulevard Ravel de Malval 42570 Saint-Héand - FRANCE Phone: +33 (0)4 77 90 78 00 Fax: +33 (0)4 77 90 78 03 angenieux@fr.thalesgroup.com Thales Angenieux in ASIA

10C Jalan Ampas #08-02 Ho Seng Lee Flatted Warehouse Singapore 329513 Phone: +65 63 56 81 98 Fax: +65 62 50 60 85 angenieux@fr.thalesgroup.com